

**YUIMA MUNICIPAL WATER DISTRICT
METER / BACKFLOW INSTALLATION CHARGES**

for parcels within the Improvement District see IDA sheet

Yuima Capacity Charges revised 3/26/10. SDCWA System Capacity Charge Amts. revised 1/1/07.

METER SIZE	5/8 x 3/4"	1"	1 1/2"	2"	3"	4"
OPERATING GPM RANGE	(30 GPM)	(3-50 GPM)	(5-100 GPM)	(5-160 GPM)	(5-350 GPM)	(5-650 GPM)
ACREAGE REQUIREMENTS <small>(meter sizes are restricted to 6 gpm/ac per resolution 702-98)</small>	Lot - 3 ac	3 to 8	8+ to 16	16+ to 20	20+ to 60	60+ to 100
COST FOR A STANDARD METER:						
Meter Installation Charge	3,100	3,300	3,800	4,800	T&M	T&M
Standard Double Check Valve *	185	200	370	450	1,300	1,850
YMWD - System Capacity Charge***	2,422	3,876	7,270	12,601	23,251	39,721
SDCWA - System Capacity Charge	4,326	6,922	12,978	22,495	41,530	70,946
SDCWA - Water Treatment Capacity Cg.	166	266	498	863	1,594	2,722
Total Deposit Required	\$10,199	\$14,564	\$24,916	\$41,209	\$67,675	\$115,239
METER COSTS WHEN THE SERVICE IS IN A SUBDIVISION WITH EXISTING SERVICE OUTLET:						
Meter Installation Charge	450	550	1,100	1,300	1,800	T&M
Standard Double Check Valve *	185	200	370	450	1,300	1,850
YMWD - System Capacity Charge***	2,422	3,876	7,270	12,601	23,251	39,721
SDCWA - Capacity Charge	4,326	6,922	12,978	22,495	41,530	70,946
SDCWA - Water Treatment Capacity Cg.	166	266	498	863	1,594	2,722
Total Deposit Required	\$7,549	\$11,814	\$22,216	\$37,709	\$69,475	\$115,239
METER COSTS WHEN GROVE WILL BE WATERED BY USING A FERTILIZER INJECTION SYSTEM:						
Meter Installation Charge	3,100	3,300	3,800	4,800	T&M	T&M
Reduced Pressure Backflow Device **	300	380	650	850	2,300	3,000
YMWD - System Capacity Charge***	2,422	3,876	7,270	12,601	23,251	39,721
SDCWA - Capacity Charge	4,326	6,922	12,978	22,495	41,530	70,946
SDCWA - Water Treatment Capacity Cg.	166	266	498	863	1,594	2,722
Total Deposit Required	\$10,314	\$14,744	\$25,196	\$41,609	\$68,675	\$116,389
PRESSURE REDUCING VALVE	60	85	220	400	900	1100
The district requires the installation of a PRV when pressure exceeds 150 psi at meter. Maximum meter operating pressure is 150 psi.						

*Double Check Valve assembly Approved by University of Southern California's List of Approved Backflow Prevention Devices

**Backflow device = Reduced Pressure Device approved by University of Southern California's List of Approved Backflow Prevention Devices

*** plus an additional charge to be determined by a study at the time of application for mtrs. 3" & larger.

A \$1,500 deposit to conduct a study is required for all meters 3" and larger and all tract maps.

T&M minimum deposit based on contractor quote for the job.

The meter installation charge is calculated to cover the cost of a typical meter installation. If the installation charges exceed the meter installation minimum deposit amount set out above (due to excess lateral, etc.) the customer will be billed for any balance due.

Maximum meter size allowed on parcel determined by parcel size. Resolution #702.98

In addition to the above pursuant to Ordinance No. 51-81 a IDA Special Connection Charge in the amount of \$2,500 per acre may be due.